LAND RECLAMATION COMMISSION

STATE OF MISSOURI

P.O. BOX 176 JEFFERSON CITY, MISSOURI 65102 573-751-4041

			Perm	it To Enga	ge in Sur	face Mining	,)	
	_		L	AND RECLAM	ATION CO	MMISSION		
				IS	SUES TO			
			LINCOI	N COUNTY	SAND &	GRAVEL, IN	1C.	
		In the apposed mining	olication, a avel operation(s	permit is herel in the stat) will be on	oy granted to e of Misson 21	to engage in sur iri. The extent of acres, mor	of the	
County	T-4-1 Cia-/Ca					Site Number		
Lincoln	USS 524	48N	02E	21	0	21	Site #1	0711
ay anno say an 1965 a		This permit may	be suspend	led or revoked	upon viola	tion of any or a	Il of the conditions set	

This permit may be suspended or revoked upon violation of any or all of the conditions set forth in "The Land Reclamation Act," RSMo. 2001, or in such rules and regulations as are promulgated pursuant thereto by the Land Reclamation Commission.

IN WITNESS WHEREOF I have hereunto set my hand this

3rd day of

September 2004

/ DIRECTOR OF STAFF
Land Reclamation Commission

Permit No. 0739

Effective Date 09/18/2004

Expiration Date 09/17/2005

RECEIVED

MISSOURI DEPARTMENT OF NATURAL RESOURCES LAND RECLAMATION COMMISSION

AUG 1 6 2004

PERMIT RENEWAL FOR INDUSTRIAL MINERAL MINES

P.O. BOX 176

	MISSOURI	LAND JEFFERSON CITY, MO 65102-0176			
NAME OF CORPORATION, COMPANY, PARTNERSHIP OR INDI	VIDUAL / RECLAMATION (COMMISSIONE & 12 04			
8 JEFFERSON AV	STATE ZIP CODE 63088				
CONTACT PERSON KEVIN TAMES	e. Valley Park	TELEPHONE NUMBER 636 225 1826 3145639962			
FEES: COMPLETE SECTION I OR SECTION	II NO				
SECTION I. Fees: Open pit operators and	those mining more than 5,000 tons of sand and	or gravel:			
1. To compute the site fee complete the in	nformation below:				
SITE NAME OR NUMBER (add a separate sheet for additional sites)	Mark each month that the site will be operated the permit year	during For sites operated less than six months per permit year pay \$150 For sites operated six months or more per permit year pay \$300			
1. LINCOLN COUNTY 5+6 SITE!	Jan, Feb Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	ov, Dec \$ 300			
2.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
3.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
4.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
5.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
6.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
7.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
8.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
9.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
10.	Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, N	lov, Dec \$			
TOTAL SITE FEE		\$'3			
2. Acreage Fee \$5 X number	of acres bonded				
3. Annual Permit Fee		\$ 500			
4. Total Fee (Add totals from 1, 2 and 3)		\$ 905			
1	en pay only	, - 0			
SECTION II. FEES: Sand or gravel operat					
1. Annual Permit Fee	organisming lead trial 10,000 tons per year.	\$ 300			
SIGNATURE OF APPLICANT	TITLE	DATE			
Korn In fam	1 P2 -	8 12 04			
Appeared before me this 1241 day of August, 2004, Kevin M. James					
to me personally known, who executed the above as their free acts and deeds.					
NOTARY PUBLIC EMBOSSER SEAL STATE OF	,	JNTY (OR CITY OF ST. LOUIS)			
SUBSCRIBED AN	D SWORN BEFORE ME, THIS	Lincoln			
		SE RUBBER STAMP IN CLEAR AREA BELOW.			
NOTARY PUBLIC	EXPIRES /	SANDRA K PARR			
Etenel	an San 6/4/05	Notary Public-Notary Seal			
' 1 1	NAME (TYPED OR PRINTED)	State of Missouri Lincoln County			
FOR DEPARTMENTAUSE ONLY, APPROVED BY	DATE APPROVED PERMIT NUMBER	My Commission Expires Jun 4, 2005			
Killing	8-30-09 073 9	7-17-05			
MO 780-1760 (12-02)					

Ł.

SITE INFORMATION FORM					
MISSOURI DEPARTMENT LAND RECLAMATION COMMISSION					
MISSOURI DEPARTMENT	ATURAL RESOURCES				

To be completed for each separate area of o	disturbance associated wi	ith mining operations	•		
SITE NAME OR NUMBER LINCON CO. SAND + GITA	Vel INC. # 1 PEI	RMIT NUMBER			
COMPANY NAME LINCON CO. SAND + GrAVE			***		
COUNTY	1/4 SECTION		SECTION)		
LINCON -	W SESTION		uss 524		
TOWNSHIP	RANGE		ACRES		
48N	2 E		1521		
RIVER OR STREAM NAME (FOR IN-STREAM ACRES)	<u></u>				
_					
MINERAL COMMODITY	ES	TIMATED TONS/YEAR (FO	R GRAVEL SITES)		
SAND+ gravel		10,000	ron your		
3					
NAME OF LANDOWNER (ATTACH LIST IF MORE THA Wende Farms INC.	N ONE)				
ADDRESS		. martin			
	1				
CITY	ST	ATE	ZIP CODE		
SOURCE OF RIGHT TO MINE (CHECK ONE):			DATE OF AGREEMENT		
MINERAL DEED	Ø	LEASE	7-8-98		
WARRANTY DEED		VERBAL AGREEMENT	, , , , ,		
OTHER (DESCRIBE):					
MINERAL RIGHTS OWNER (ATTACH LIST IF MORE T	HAN ONE)				
SAME	v				
ADDRESS					
CITY	ST	ATE	ZIP CODE		
SOURCE OF RIGHT TO MINE (CHECK ONE):					
MINERAL DEED		LEASE	7-8-98		
WARRANTY DEED VERBAL AGREEMENT					
OTHER (DESCRIBE):					
NOTE: Each site must be shown on a map	and be included in a publ	lic notice and an appr	oved mine plan.		





P.O. BOX 176 JEFFERSON CITY, MO 65102

TYPE OF PLAN (CHECK ONE):		
SHORT TERM, FOR ONE PERMIT YEAR	COMPANY NAME LINCON	LO. SAND + grave INC.
LONG TERM, FOR PERIOD THROUGH DATE: 7/		/
DESCRIPTION OF SITE PRIOR TO LAND RECLAMATIC AND TOPOGRAPHY.		PRIOR OPERATOR), INCLUDING SOIL, VEGETATION
•	eds live the Pit ANA	İ
to the west Boundry 15	INDUSTRIAL Thereare	OALSES ON The
west side of the Re	ermit that were mined	Prior to 1972
	-/	11101 10 1912
		!
OPERATION PLAN - 10 CSR 40-10 020/2)/F		
OPERATION PLAN - 10 CSR 40-10.020(2)(E))1.	
OPERATION PLAN - 10 CSR 40-10.020(2)(CA. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECI		IS TOPSOIL TO BE SOLD OR DISCARDED OFFSITE?
A. TOPSOIL	LAMATION COMMISSION PERMITTING	IS TOPSOIL TO BE SOLD OR DISCARDED OFFSITE?
A. TOPSOIL		IS TOPSOIL TO BE SOLD OR DISCARDED OFFSITE?
A. TOPSOIL	LAMATION COMMISSION PERMITTING 1-10 INCHES	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECI	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	
A. TOPSOIL AVERAGE DEPTH OF TOPSOIL, PRIOR TO LAND RECE DESCRIBE METHODS AND EQUIPMENT USED FOR TO	LAMATION COMMISSION PERMITTING 1-10 INCHES DPSOIL REMOVAL	

DESCRIBE METHODS AND EQUIPMENT USED FOR TOPSOIL STORAGE AND PROTECTION

The scraper will deposit the Soil IN Stock Bles Near the Pit Area the stock Piles + Bern will be shalled and seeded with grasses. To Protect exosion or AS A Perimeter Bern

DESCRIBE METHODS AND LOCATION OF SPOIL PLACEMENT AND DISPOSAL OVEY BURLEN YE MOVED MINISTERNAL C. ACID MATERIALS DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW) NOW D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCREELGZ-TION AND CRIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS Will any excavation be at or within fifty feet (50°) of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials be left within fifty feet of the right-of-way start near fire right of way, and in no case may the excavation be closer to the right of way, and in no case may the execution be closer to the right of way, and in no case may the execution be closer to the right of way, and in no case may the execution be closer to the right of way, and in no case may the execution be closer to the right of way, and in no case may the execution be closer to the right of way, than lifty feet or twenty-live feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is greater, unless a variance is granted by the Commission.)			
OVER BUILDING YEAR ON SITE MAPS C. ACID MATERIALS DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE-NONE' BELOW) WOW D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of wey than fifty the refuse or twenty-five feet plus one and one-half (1-b) times the depth of unconsolidated materials without provided that the right of way than fifty the feet plus one-solidated materials. Whichever is	B. SPO	IL	
C. ACID MATERIALS DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! WOW D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? Will any highwait consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right way than they start near the right of way, and in no case may the excavation be closer to the right way than they start near the right of way, and in no case may the excavation be closer to the right way than they start near the right of way. Then they start near the right of way, and in no case may the excavation be closer to the right with where they are they feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	DESCRIB	E METHOD	S AND LOCATION OF SPOIL PLACEMENT AND DISPOSAL
C. ACID MATERIALS DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE 'NONE' BELOW) WOW D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LCC_ATION AND ORIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS Will any excavation be at or within fifty feet (50°) of the right-of-way of any public road? Will any highweal consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way, and in no case may the excavation be closer to the right of way, and in no case may the excavation be closer to the right of way, and in no case may the excavation be closer to the right of way, and in no case may the excavation be closer to the right of way start near the right of way, and in no case may the excavation be closer to the right of way and in no case may the excavation be closer to the right of way.			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	41	and re	ec lamation
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
DESCRIBE METHODS AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW! ### DESCRIBE LOCATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS ### Will any excavation be at or within fifty feet (50") of the right-of-way of any public road? ### Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials teft in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	C. ACIE	MATER	IALS
D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	DESCRIBE	METHOD	AND EQUIPMENT USED FOR HANDLING ACID MATERIALS (IF NONE IS ANTICIPATED, WRITE "NONE" BELOW)
D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
D. PIT INFORMATION (GIVE ALL DIMENSIONS IN FEET) DESCRIBE LOCATION AND ORIENTATION OF PIT. IF NOT CLEAR ON SITE MAPS YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is		NO	ν_{e}
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	:		
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
YES NO ☐ ☑ Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? ☐ Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	DESCRIE	LOCATIO	NAND CHIENTATION OF PIT, IF NOT CLEAR ON SITE MAPS
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any excavation be at or within fifty feet (50') of the right-of-way of any public road? Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			
Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is	YES	NO	
Will any highwall consisting of unconsolidated materials be left within fifty feet of the right-of-way of any public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is			Will any excavation be at or within fifty feet (50') of the right-of-way of any public road?
public road? (NOTE: For unconsolidated materials left in place, a slope of no more than forty degrees may start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-1/2) times the depth of unconsolidated material, whichever is			will any excavation be at or within inty feet (50) of the right-of-way of any public road?
start near the right of way, and in no case may the excavation be closer to the right of way than fifty feet or twenty-five feet plus one and one-half (1-½) times the depth of unconsolidated material, whichever is		\boxtimes	
or twenty-five feet plus one and one-half (1-1/2) times the depth of unconsolidated material, whichever is			
☑ Will any excavation start at or within fifty feet (50') of any property line?	⊠		Will any excavation start at or within fifty feet (50') of any property line?
(NOTE: If the answer is "yes", a safety barrier may be needed.)	7		

PAGE 2 OF 5

MO 780-1327 12-91

DESCRIBE METHODS AND EQUIPMENT TO BE USED FOR SEEDING OR PLANTING during the FIRST spring FAllowing Tol Soil rellacement the seed MIX will be proadcast and harrowed After grasses have grown GAFFKIENT to control erasion trees or schrurs will be hand Planted Lime and fertilizer will be applied according to recommendations made, based on an analysis of soil texture and nutrients. Mulch will be applied to all slopes exceeding 5:1. **SEEDED SPECIES** POUNDS/ACRE TREE OR SHRUB SPECIES STEMS/ACRE Gilver Marle orchord grass 10 PIN OAK B 10 100 KoreAN LEGREDESA 10 Red clover 2 REVEGETATION MIX =2 = _ RPOSE OR LAND USE B SEEDING OR PLANTING TIME DESCRIBE METHODS AND EQUIPMENT TO BE USED FOR SEEDING OR PLANTING Lime and fertilizer will be applied according to recommendations made, based on an analysis of soil texture and nutrients. Mulch will be applied to all slopes exceeding 5:1. SEEDED SPECIES STEMS/ACRE POUNDS/ACRE TREE OR SHRUB SPECIES

RECLAMATION PLAN - 10 CSR 40-10.020(2)(D)2.

REVEGETATION MIX #1

A. REVEGETATION (Attach additional sheets, if needed)

ATTACH ADDITIONAL SHEETS FOR ADDITIONAL SEED MIXES.

MO 780-1327 (12-91)

PURPOSE OR LAND USE

B. SEEDING OR PLANTING TIME

PAGE 3 OF 5

R	_	8		-	ш	IG
ь.		_	-	u		

DESCRIBE PROPOSED RECLAIMED TOPOGRAPHY, INCLUDING SLOPES

All shall Area & will be graded to slokes traversable by FARM Machinery
A lake will be constructed in the Final Pit Area the lake will be
designed and constructed to meet ses standards

_					
C	. DESCRIBE	E THE GENERA	L SEQUENCE AND	TIMING OF THE FOLI	LOWING ACTIVITIES

grading will be done As the Pit Advances and the Sollighand in the Mundo out Portions. Final grading will be confleted with in 1 year of ATRAS Becoming water

REPLACEMENT OF TOPSOIL

The Sollwill Be replaced within 12 months of Areas becoming INACTIVE

REVEGETATION

All tol goil Area will be seeded during the First offmum seeding Period Fallowing Tol goil rellacement

AVERAGE DEPTH OF REPLACED TOPSOIL (INCHES)

12

Estimate acreage of each land use below, after reclamation	ESTIMATED ACRES:
Wildlife (forest or other habitat with livestock excluded)	5
Agricultural (pasture, cropland, and horticultural)	
Development (residential, industrial, and recreational)	
Water impoundments (for wildlife, agricultural, or development)	16

By my signature, I attest to the following:

MO 780-1327 (12-91)

- 1. All statements made on this Mine Plan Form are correct, complete, and true, to the best of my knowledge.
- 2. I or the company I am authorized to represent intend(s) to mine in accordance with this Mine Plan Form, and in accordance with the Missouri Land Reclamation Act, Sections 444.760 through 444.789, RSMo and all rules, regulations, orders, decisions and permits of the Missouri Land Reclamation Commission pertaining to my company's surface mining operations.
- 3. I have obtained the approval of all landowner's for all proposed post-reclamation land uses.
- 4. I have a valid agreement with all landowners which gives me the right to grant access to the Director of the Missouri Land Reclamation Commission and his authorized representatives, and I grant such access, and further where I have no such right, I have attached signed affidavits from the landowners, granting such access.

SIGNATURE OF APPLICANT		TITLE	DATE
Kern m James	_	Pres	72798
NOTARY PUBLIC EMBOSSER SEAL	SUBSCRIBED AND SWORN B	EFORE ME, THIS	COUNTY (OR CITY OF ST. LOUIS)
	27th DAY	OF July 1998	USE RUBBER STAMP IN CLEAR AREA BELOW
	NOTARY PUBLIC SIGNATURE NOTARY PUBLIC NAME (TYPED O	Frantham 2/7/99 Brantham 2/7/99 Brantham 2/7/99	SHIRLEY L. GRANTHAM TARY PUBLIC STATE OF MISSOURI COUNTY OF COLE WY GOMMISSION EXPIRES: EEBRUARY 7, 1999
APPROVED BY (DIRECTOR'S RE	PRESENTATIVE)	DATE APPROVED	PERMIT NUMBER
les 1 B		9-17-9	12 273 7

